

# **Factory Installed Panel Mount**

# BOURNS

# TRIMPOT® POTENTIOMETER PANEL MOUNTING OPTIONS AND HARDWARE

Many Trimpot® Potentiometers are available for panel mount application.

This product option provides for maximum design flexibility.

To order Trimpot® Potentiometers with panel mount hardware attached by the factory, simply add an "M" or "Z" suffix to the Bourns part number per Table I.

Example: 3006P-1-100Z

To order military Trimpot® Potentiometers with panel mount hardware attached by the factory, order the military part number and add "with panel mount attached."

Example:

RT12C2PRC, with panel mount attached.


To order panel mounting accessories for customer installation, simply use the part number per Table II.


Example: H83P


NOTE: For complete product specifications, see data sheet for the trimmer model.

Torque - Apply maximum 8 in. lbs. on mounting nut when mounted on panel.


#### Models RT12/RJ12, 3057/3059









#### Models 3005/3006/3009







#### NOTES:

- PROVIDED WITH LOCKWASHER AND MOUNTING NUT.
- 2. RECOMMEND PANEL HOLES. #10 DRILL  $\frac{.194}{(.008)}$

#### NOTES:

- 1. PROVIDED WITH LOCKWASHER AND MOUNTING NUT.
- 2. RECOMMEND PANEL HOLE SIZE #7 DRILL  $\frac{.200}{(.008)}$









# **Factory Installed Panel Mount**


# BOURNS®

#### Models 3292

X, L and W Styles










#### NOTES:

1. PROVIDED WITH LOCKWASHER AND MOUNTING NUT.

#### Models RT22/RTR22/RJ22 3250/3252









#### NOTES:


1. PROVIDED WITH LOCKWASHER AND MOUNTING NUT.

#### Models RT24/RTR24/3290

H and W Styles - 3290 X & W Styles-RT24/RTR24








#### NOTES:

1. PROVIDED WITH LOCKWASHER AND MOUNTING NUT.








# **Customer Installed Panel Mount - Unsealed**


# BOURNS


#### SEE TABLE II FOR PANEL MOUNT PART NUMBER

#### H-58P Panel Mount

1-1/4 Inch Rectangular Multiturn Modules








#### NOTES:


- 1. PROVIDED WITH LOCKWASHER AND MOUNTING NUT.
- 2. RECOMMEND PANEL HOLES. #10 DRILL  $\frac{.194}{(.008)}$


\*SPECIFY H82 IF PANEL SEAL IS REQUIRED.

#### H-65P Panel Mount

1/2 Inch Square Multiturn Models








#### NOTES


- 1. PROVIDED WITH LOCKWASHER AND MOUNTING
- 2. DRAWINGS SHOWN WITH TRIMMER. ORDER PART SEPARATELY


#### H-83P Panel Mount

Adapter for Models 3005 AND 3006

The H-83P Adapter is used with Models 3005 and 3006. Order separately and simply snap fit the trimmer in the plastic case. The H-83P with lock-washer and mounting nut is available in 50-piece lots.







#### NOTES:

1. DRAWINGS SHOWN WITH TRIMMER. ORDER PART SEPARATELY





# **Customer Installed Panel Mount**


### BOURNS

#### H-114P/115P/116P Panel Mount

#### 3/8 Inch Square Multiturn Models









#### Notes:


- 1. Provided with lockwasher and mounting nut.
- 2. Drawings shown with trimmer. Order part separately.

#### H-117P Panel Mount

#### 3/8 Inch Square Multiturn Models







#### Notes:

- 1. Provided with lockwasher and mounting nut.
- 2. Drawings shown with trimmer. Order part separately.

#### TABLE I FACTORY INSTALLED PANEL MOUNTS

|                        | P/N WITH                 |  |  |
|------------------------|--------------------------|--|--|
| STANDARD P/N           | PANEL MOUNT              |  |  |
| 3005P-1-(RC)           | 3005P-1-(RC) Z           |  |  |
| 3006P,Y, or W-1-(RC)   | 3006P,Y, or W-1-(RC) Z   |  |  |
| 3009P or Y-1-(RC)      | 3009P or Y-1-(RC) Z      |  |  |
| 3057L,J,P, or Y-1-(RC) | 3057L,J,P, or Y-1-(RC) M |  |  |
| 3059L,J,P, or Y-1-(RC) | 3059L,J,P, or Y-1-(RC) M |  |  |
| 3250L or W-1-(RC)      | 3250L or W-1-(RC) M      |  |  |
| 3252L or W-1-(RC)      | 3252L or W-1-(RC) M      |  |  |
| 3290 H or W-1-(RC)     | 3290H or W-1-(RC) M      |  |  |
| 3292L,W, or X-1-(RC)   | 3292L,W, or X-1-(RC) M   |  |  |
| 3296W or X-1-(RC)      | 3296W or X-1-(RC) M      |  |  |

# TABLE II RETRO-FIT PANEL MOUNTS FOR INSTALLATION BY CUSTOMER

|                        | ORDER PANEL MOUNT  |  |  |
|------------------------|--------------------|--|--|
| STANDARD P/N           | P/N                |  |  |
| 3005P-1-(RC)           | H-83P              |  |  |
| 3006P,Y, or W-1-(RC)   | H-83P              |  |  |
| 3057L,J,P, or Y-1-(RC) | H-58P* SCREW ASSY. |  |  |
| 3059L,J,P, or Y-1-(RC) | H-58P* SCREW ASSY. |  |  |
| 3250L, W, X-(RC)       | H-65P-1*           |  |  |
| 3252L or W-1-(RC)      | H-65P-3*           |  |  |
| 3252X-1-(RC)           | H-65P-5*           |  |  |
| 3290 H or W-1-(RC)     | H-114P*            |  |  |
| 3292L-1-(RC)           | H-115P*            |  |  |
| 3292W OR X-1-(RC)      | H-116P*            |  |  |
| RT12P,Y,L              | H-58P* SCREW ASSY. |  |  |
| RJ12P,Y                | H-58P* SCREW ASSY. |  |  |
| RT22L,W, X,            |                    |  |  |
| RTR22L,W, X            | H-65P-1*           |  |  |
| RJ22L,W                | H-65P-3*           |  |  |
| RJ22X                  | H-65P-5*           |  |  |
| RT24W /                |                    |  |  |
| RTR24W OR X            | H-114P*            |  |  |
| RJR24W OR X            | H-117P*            |  |  |

\*Specify H-82 if panel seal is required.






# **Hardware For Special Mounting Applications**

### BOURNS®

#### H-82 Panel Seal

For all panel mounts with size 10-32 bushings.





To be used with the following to provide panel seal:

H-58P

H-65P-1

H-65P-3

H-65P-5


H-114P

H-115P H-116P

H-117P

#### H-25/H-28 Stacking Straps

Models 3250, 3252 (H-25) and 3292 (H-28).



| DIMENSIONS | H-25                  | H-28                  |
|------------|-----------------------|-----------------------|
| А          | .236<br>(.093)        | .178<br>(.070)        |
| В          | <u>.363</u><br>(.143) | <u>.318</u><br>(.125) |
| С          | 1.321<br>(.520)       | 1.064<br>(.419)       |
| THICKNESS  | <u>.51</u><br>(.02)   |                       |