

SMA Female Right Angle Connector Solder Attachment Thru Hole PCB, .200 inch x .067 inch Hole Spacing



TECHNICAL DATA SHEET

PE4118

SMA Female Right Angle Connector Solder Attachment Thru Hole PCB, .200 inch x .067 inch Hole Spacing

Configuration

Connector

Connector SMA Female
Connector Specification

MIL-STD-348
Connector Interface Type
Cable Attachment Method (Shield/Contact)

Body Style

SMA Female
MIL-STD-348
Thru Hole
Solder
Roght Angle

Electrical Specifications

Frequency Range, GHz DC to 12.4 Impedance, Ohms 50 Maximum VSWR 1.25:1

Mechanical Specifications

Size

 Length, in [mm]
 0.55 [13.97]

 Width/Dia., in [mm]
 0.25 [6]

 Height, in [mm]
 0.5 [12.7]

 Weight, lbs [g]
 0.006 [2.72]

Connector

Type SMA Female
Contact Material and Plating Beryllium Copper, Gold
Contact Plating Specification MIL-G-45204
Body Material and Plating Stainless Steel, Gold
Body Plating Specification MIL-G-45204
Dielectric Type Teflon

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/sma-female-standard-thru-hole-pcb-connector-pe4118-p.aspx

SMA Female Right Angle Connector Solder Attachment Thru Hole PCB, .200 inch x .067 inch Hole Spacing from Pasternack Enterprises has same day shipment for domestic and International orders. We maintain 99% availability of the industry's broadest selection of RF, microwave and fiber optic products.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE4118 CAD Drawing

SMA Female Right Angle Connector Solder Attachment Thru Hole PCB, .200 inch x .067 inch Hole Spacing

