



- NOTES:
1. ALL DIMENSION IN MM [INCH]
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. TERM. NOS. FOR REF. ONLY
 4. CONTACT RATING SWITCHING: 150mA, 250V AC/DC
350mA, 110V AC/DC
 5. CONTACT RATING (NON-SWITCHING) 5A
 6. CONTACT MATERIAL: SILVER over COPPER ALLOY.
 7. OPERATING FORCE: 425±100 CM/STANDARD
 8. OPERATING TEMP: -30° to 85°C
 9. CIRCUIT SP: 8 POSITIONS, 30° INDEX.
 10. DIELECTRIC STRENGTH 1000V RMS min. @ SEA LEVEL
 11. ▲ DENOTES CRITICAL PARAMETER.
 12. HARDWARE SUPPLIED ON SWITCH— SEE BELOW STOPRING, LOCKWASHER & HEX NUT



E-SWITCH®

B	13312	6.00 WAS 6.35, 15.00 WAS 16.00	7/24/03	AR
A	13304	RELEASED FOR PRODUCTION	7/18/03	AR
REV.	ECN No.	DESCRIPTION	DATE	CHKD

TITLE		KC18B7.002NLS		
SCALE	DATE	DR	DWG	REV
1.5:1	7/18/03	AR	G530171	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED