



- NOTES:
- ALL DIMENSIONS IN MM
  - GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
  - RATING: 50mA @ 12VDC
  - TRAVEL: 0.25 +0.2/0.1mm
  - OPERATING FORCE: 160±50gf
  - CONTACT RESISTANCE: 100 Milli-Ohms Max
  - 2002/95/EC (ROHS) COMPLIANT
  - SHORTER LEAD (WITH COLOR) IS NEGATIVE (CATHODE).
  - ▲ DENOTES CRITICAL PARAMETER

LED SPECS	UNITS	BLUE
FORWARD CURRENT	mA	20
FORWARD VOLTAGE	V	3.2-4.0
LUMINOUS INTENSITY	MCD	500



TITLE TL1240BQ1JCLR

B	19550	DRAWING UPDATE / CLEAN-UP	12/28/10	BGL
A	18069	RELEASED FOR PRODUCTION	5/6/08	BLR
REV	PCR NO	DESCRIPTION	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

SCALE 4:1 DATE 5/6/2008 DR BLR DWG XP0059P

REV B