

MBRP30045CT

POWERTAP II Switch-mode Power Rectifier

These state-of-the-art devices use the Schottky Barrier principle with a platinum barrier metal.

Features

- Dual Diode Construction – May Be Paralleled for Higher Current Output
- Guardring for Stress Protection
- Low Forward Voltage
- 150°C Operating Junction Temperature
- Guaranteed Reverse Avalanche
- Pb-Free Package is Available*

Mechanical Characteristics:

- Case: Epoxy, Molded with metal heatsink base
- Weight: 80 grams (approximately)
- Finish: All External Surfaces Corrosion Resistant
- Top Terminal Torque: 25–40 lb-in max
- Base Plate Torques:
See procedure given in the Package Outline Section

MAXIMUM RATINGS

| Rating | Symbol | Max | Unit |
|--|-------------|-----------------------|------------------|
| Peak Repetitive Reverse Voltage | V_{RRM} | 45 | V |
| Working Peak Reverse Voltage | V_{RWM} | | |
| DC Blocking Voltage | V_R | | |
| Average Rectified Forward Current (Rated V_R , $T_C = 140^\circ\text{C}$) | $I_{F(AV)}$ | 150 300 | A A |
| | | Per Leg Per Device | |
| Peak Repetitive Forward Current, (Rated V_R , Square Wave, 20 kHz, $T_C = 140^\circ\text{C}$) | I_{FRM} | 300 | A |
| | | Per Leg | |
| Non-Repetitive Peak Surge Current (Surge Applied at Rated Load Conditions Halfwave, Single Phase, 60 Hz) | I_{FSM} | 2500 | A |
| | | Per Leg | |
| Peak Repetitive Reverse Current (2.0 μs , 1.0 kHz) | I_{RRM} | 2.0 | A |
| | | Per Leg | |
| Storage Temperature Range | T_{stg} | -55 to +150 | $^\circ\text{C}$ |
| Operating Junction Temperature | T_J | -55 to +150 | $^\circ\text{C}$ |
| Voltage Rate of Change (Rated V_R) | dv/dt | 10,000 | V/ μs |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.


*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.



ON Semiconductor®


www.onsemi.com

SCHOTTKY BARRIER RECTIFIER 300 AMPERES, 45 VOLTS



POWERTAP II
CASE 357C
PLASTIC

MARKING DIAGRAM



B30045T = Specific Device Code
MCC = Mold Compound Code
A = Assembly Location
YY = Year
WW = Work Week
G = Pb-Free Package

ORDERING INFORMATION

| Device | Package | Shipping |
|--------------|--------------------------|---------------|
| MBRP30045CT | POWERTAP II | 25 Units/Tray |
| MBRP30045CTG | POWERTAP II (Pb-Free) | 25 Units/Tray |

MBRP30045CT

THERMAL CHARACTERISTICS (Per Leg)

| Rating | Symbol | Value | Unit |
|--------------------------------------|-----------------|-------|-----------------------------|
| Thermal Resistance, Junction-to-Case | $R_{\theta JC}$ | 0.45 | $^{\circ}\text{C}/\text{W}$ |

ELECTRICAL CHARACTERISTICS (Per Leg)

| | | | |
|--|-------|--------------|----|
| Instantaneous Forward Voltage (Note 1) ($i_F = 150$ Amps, $T_J = 25^{\circ}\text{C}$) ($i_F = 300$ Amps, $T_J = 25^{\circ}\text{C}$) | V_F | 0.70 0.82 | V |
| Instantaneous Reverse Current (Note 1) (Rated dc Voltage, $T_J = 125^{\circ}\text{C}$) (Rated dc Voltage, $T_J = 25^{\circ}\text{C}$) | i_R | 75 0.8 | mA |


Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

1. Pulse Test: Pulse Width = 300 μs , Duty Cycle $\leq 2.0\%$.

MAXIMUM MECHANICAL RATINGS

| | |
|-------------------------------------|---|
| Terminal Penetration: | 0.235 max |
| Terminal Torque: | 25–40 in-lb max |
| Mounting Torque — Outside Holes: | 30–40 in-lb max |
| Mounting Torque — Center Hole: | 8–10 in-lb max |
| Seating Plane Flatness | 1 mil per in. (between mounting holes) |

POWERTAP MECHANICAL DATA APPLIES OVER OPERATING TEMPERATURE



Note: While the POWERTAP is capable of sustaining these vertical and levered tensions, the intimate contact between POWERTAP and heat sink may be lost. This could lead to thermal runaway. The use of very flexible leads is recommended for the anode connections. Use of thermal grease is highly recommended.


MBRP30045CT

MOUNTING PROCEDURE

The POWERTAP package requires special mounting considerations because of the long longitudinal axis of the copper heat sink. It is important to follow the proper tightening sequence to avoid warping the heat sink, which can reduce thermal contact between the POWERTAP and heat sink.


STEP 1:

Locate the POWERTAP on the heat sink and start mounting bolts into the threads by hand (2 or 3 turns).




STEP 2:

Finger tighten the center bolt. The bolt may catch on the threads of the heat sink so it is important to make sure the face of the bolt or washer is in contact with the surface of the POWERTAP.




STEP 3:

Tighten each of the end bolts between 5 to 10 in-lb.




STEP 4:

Tighten the center bolt between 8 to 10 in-lb.



STEP 5:


Finally, tighten the end bolts between 30 to 40 in-lb.



MBRP30045CT

PACKAGE DIMENSIONS

CASE 357C-03
 POWERTAP
 PLASTIC PACKAGE
 ISSUE E



NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. TERMINAL PENETRATION: 5.97 (0.235) MAXIMUM.

| DIM | INCHES | | MILLIMETERS | |
|-----|--------------|--------------|-------------|-------|
| | MIN | MAX | MIN | MAX |
| A | 3.450 | 3.635 | 87.63 | 92.33 |
| B | 0.700 | 0.810 | 17.78 | 20.57 |
| C | 0.615 | 0.640 | 15.63 | 16.26 |
| E | 0.120 | 0.130 | 3.05 | 3.30 |
| F | 0.435 | 0.445 | 11.05 | 11.30 |
| G | 1.370 | 1.380 | 34.80 | 35.05 |
| H | 0.007 | 0.030 | 0.18 | 0.76 |
| N | 1/4-20UNC-2B | 1/4-20UNC-2B | | |
| Q | 0.270 | 0.285 | 6.86 | 7.23 |
| R | 31.50 BSC | 80.01 BSC | | |
| U | 0.600 | 0.630 | 15.24 | 16.00 |
| V | 0.330 | 0.375 | 8.39 | 9.52 |
| W | 0.170 | 0.190 | 4.32 | 4.82 |

ON Semiconductor and the are registered trademarks of Semiconductor Components Industries, LLC (SCILLC) or its subsidiaries in the United States and/or other countries. SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
 Literature Distribution Center for ON Semiconductor
 P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
 USA/Canada
Europe, Middle East and Africa Technical Support:
 Phone: 421 33 790 2910
Japan Customer Focus Center
 Phone: 81-3-5817-1050

ON Semiconductor Website: www.onsemi.com
Order Literature: <http://www.onsemi.com/orderlit>
 For additional information, please contact your local Sales Representative