






# VL Plus Whites

## Everyday standard face lit solutions

VL Plus LED lighting system is based on proven SloanLED channel letter module design and performance. VL Plus offers a variety of solutions and a wide selection of color temperatures.

- Short available in 5 shades of white
- Constant Current Technology (CCT)

### Specifications



<b>Part number</b>	Long	6500 K	701269-WVLL-MB
	Short	7200 K	701269-7WSA1-MB
		6500 K	701269-WVLS-MB
	5000 K	701269-5WSA1-MB	
	4000 K	701269-4WSA1-MB	
<b>Dimensions L × W × H</b>	Mini	3000 K	701269-3WSA1-MB
		6500 K	701269-WVLM-MB
	Long		3.45 in × 0.49 in × 0.35 in
Short		2.35 in × 0.49 in × 0.35 in	
Mini		1.33 in × 0.44 in × 0.35 in	
<b>Viewing angle</b>		120°	
<b>LEDs per module</b>	Long/Short	3	
	Mini	2	
<b>Modules per foot</b>	Long	2	
	Short	2.5	
	Mini	4	
<b>Maximum coverage per row</b>	<b>Can depth</b>	<b>Coverage</b>	
	5 in	5 in	
<b>Operating temperature</b>	-40° C to +70° C		
<b>Protection class</b>	IP66		
<b>Power per module</b>	Long/Short	0.36 W	
	Mini	0.28 W	
<b>Efficacy</b>	Long/Short	111 lm/W	
	Mini	71 lm/W	
<b>Power capacity</b>	Per SloanLED 60 W 12 VDC power supply:		
	Long/Short	150 modules	
	Mini	196 modules	
<b>Fastening</b>	Peel-n-stick and mechanical		



# VL Plus Whites

Everyday standard face lit solutions

## Specifications *cont'd*

### Packaging

5 trays per carton	
Long	25 ft (50 modules) per tray
Short	30 ft (75 modules) per tray
Mini	25 ft (100 modules) per tray



Size	Color temperature	Part number	Lumens per module (nominal)
Long	6500 K	701269-WVLL-MB	40
Short	7200 K	701269-7WSA1-MB	40
	6500 K	701269-WVLS-MB	40
	5000 K	701269-5WSA1-MB	40
	4000 K	701269-4WSA1-MB	40
	3000 K	701269-3WSA1-MB	40
Mini	6500 K	701269-WVLM-MB	20

