



All dimensions are in mm; tolerances according to ISO 2768 m-H

**Interface**

According to IEC 60169-4, VG 95250, EN 122190, DIN 47223

**Documents**

N/A

**Material and plating**

**Connector parts**

Center conductor  
Outer conductor  
Dielectric  
Substrate

**Material**

Beryllium copper  
Brass  
PPE  
Al<sub>2</sub>O<sub>3</sub>

**Plating**

Silver, 3-6 µm  
Flash white bronze over silver(e.g. Optargen®)

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF\_35/05.10/6.0

**Electrical data**

Frequency range DC to 3 GHz  
 Return loss  $\geq 34.1$  dB, DC to 2 GHz  
 $\geq 26.0$  dB, 2 GHz to 3 GHz  
 DC Resistance 50  $\Omega$   
 Power handling  $\leq 2$  W at 25°C  
 derated linearity to 0 Watts at 85°C

**Mechanical data**

Mating cycles  $\geq 500$   
 Coupling nut retention  $\geq 1000$  N  
 Recommended torque 25 to 30 Nm  
 Proof torque  $\leq 35$  Nm

**Environmental data**

Operating temperature range<sup>1</sup> -40 °C to +85 °C  
 Storage temperature range -40 °C to +85 °C  
 2002/95/EC (RoHS) compliant

<sup>1</sup> Temperature range over which these specifications are valid.

**Packing**

Standard 1 pce in bag  
 Weight 85 g/pce

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF\_35/05.10/6.0

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Kerstin Herzog	28/07/05	Frank Weiß	23/05/12	b00	12-0448	Marion Striegler	23/05/12
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany <a href="http://www.rosenberger.de">www.rosenberger.de</a>				Tel. : +49 8684 18-0 Fax : +49 8684 18-499 Email : <a href="mailto:info@rosenberger.de">info@rosenberger.de</a>			Page 2 / 2