



IEC-4000 [?][?][?][?]: 1

Industrial Fast Ethernet mini Media Converter - 10/100Mbps RJ-45 Copper to 100Mbps SFP Fiber

LevelOne IEC-4000 is an industrial Fast Ethernet media converter with a mini size, rugged aluminium case which providing superb heat dissipation. This converter is designed to be mounted on an industrial standard DIN-rail, as well as on the wall, plus the clearly visible status LEDs provide simple monitoring of port link activity. It also features Link Fault Pass Through in order to alert remote location when link status changes.

Key Features

- 10/100BaseT to 100Base-FX
- Rugged aluminium case design in a mini size form factor
- 18V-36VAC & 12V-60VDC with polarity protection
- Link Fault Pass through (LFP) function
- Supports switch and pure converter mode
- Surge & ESD protection
- Maximum noise & interference immunity
- -40°C to 75°C (-40°F to 167°F) operating temperature range
- DIN-Rail or panel mount installation



System Specifications

Standards & Protocols:

IEEE 802.3 10-BASE-T, Ethernet
 IEEE 802.3u 100-BASE-TX, Fast Ethernet
 IEEE 802.3u 100-BASE-FX, Fast Ethernet
 IEEE 802.3x Flow Control and Back Pressure

Connectors and Cabling:

Ethernet Port: 10/100Mbps RJ45
 - Auto Speed negotiation
 - Auto MDI/MDI-X
 - Full/Half Duplex
 Fibre Port: 100Base-X SFP Slot

Indicator:

Power, Speed (TP), Link / Act (TP & Fibre)

Transmission Method:

Store and forward (Default) pass through

**Power:**

Power Consumption: 1.44W

Power Input:

12 to 60VDC or 18 to 36VAC (Terminal Block)

Dual power input capable (Redundancy)

Features**General:**

DIP Switch:

Link Fault Pass Through (LFP) Enable / Disable

Switch Converter / Pure Converter mode

Performance**Operating Distance:**

depend on SFP module

Environment**Temperature (°C):**

Storage: -40 ~75 °C

Operating: -40 ~ 75 °C

Humidity (Non-condensing):

5 ~ 95 %

Physical Specifications**Dimensions (W x D x H mm):**

59 x 49 x 36mm

Weight (g):

gross weight 260g, Net weight 90g

Others**Approval and Compliance:**

FCC Part 15 Subpart B Class A

CE EN 55022 Class A

FCC Part 15 Subpart B Class A,

CE EN 55022 Class A

EN61000-4-2 (ESD) Level 3

EN61000-4-3 (RS) Level 2

EN61000-4-4 (EFT) Level 2

EN61000-4-5 (Surge) Level 2

EN61000-4-6 (CS) Level 2

EN 61000-4-8 (PFMF) Level 1

UL508 (Pending)

EN 50121-4 (Pending)

IEC 60068-2-27

IEC 60068-2-32

IEC 60068-2-6


RoHS / REACH

Deployment:

Desk, wall and chassis mounted



Unit: mm



Order Information

IEC-4000

Package Contents

IEC-4000

Quick Installation Guide



POW-1212

Industrial Power Adapter, Open Wire Ends, 36W, 12VDC



POW-4801

48V DC Power Adapter

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.