


SERIES R1612



● **FEATURES**

- ULTRA SMALL ULTRA THIN
- AUTOMATIC MOUNTING POSSIBLE
- REFLOW POSSIBLE
- EXCELLENT FOR HIGH DENSITY APPLICATIONS



● **SPECIFICATIONS**

PARAMETER	VALUE
FREQUENCY RANGE	24.000 MHz to 60.000 MHz
MODE OF OSCILLATION	AT CUT, Fundamental
FREQUENCY TOLERANCE AT 25°C	±50 ppm max ±10ppm, ±20ppm, ±30 ppm available
FREQUENCY STABILITY OVER TEMPERATURE	±50 ppm max ±10ppm, ±20ppm, ±30 ppm available
OPERATING TEMPERATURE RANGE	-10°C to +60°C Standard -40°C to +85°C Extended
STORAGE TEMPERATURE RANGE	-40°C to +85°C
AGING	±2 ppm per year
LOAD CAPACITANCE	8 pF to 32 pF or Series Resonance
EQUIVALENT SERIES RESISTANCE	See Table 1
SHUNT CAPACITANCE	3.5 pF max
DRIVE LEVEL	50 µW max

TABLE 1		
FREQUENCY (MHz)	MODE	MAXIMUM ESR (Ω)
24.000 to 40.999	FUND	150
41.000 to 60.000	FUND	100

■ **PART NUMBERING SYSTEM**

TYPE	-	FREQUENCY	-	LOAD CAPACITANCE	-	MODE	TOLERANCE/STABILITY (PPM/PPM)
R1612	-	IN MHz	-	8 to 32 pF for PARALLEL S for SERIES	-	Blank for < 24.576 MHz F for ≥ 24.576 MHz	Blank for MAXIMUM PPMPPM for OTHER Example: 1020, 2050


-	TEMPERATURE RANGE	-	TAPE & REEL
-	Blank for STANDARD EXT for EXTENDED	-	TR

EXAMPLE: R1612-26.000-8-F-1530-TR


Surface Mount Crystal, 1.6 x 1.2 mm, 26.000 MHz, 8 pF Load, Fundamental Mode, ±15 ppm Tolerance, ±30 ppm Stability, from -10°C to +60°C, Tape and reel Packaging

SERIES R1612

MECHANICAL SPECIFICATION



CARRIER TAPE DIMENSIONS




NOTE: REFER TO EIA-481 FOR NON-SPECIFIED DIMENSIONS

PACKAGING

180 mm REEL DIAMETER
 8 mm TAPE WIDTH, 4 mm PITCH
 QUANTITY: 3000 PIECES PER REEL

● REFLOW PROFILE



Reflow profile		
Temperature Min Preheat	T _{SMIN}	150°C
Temperature Max Preheat	T _{SMAX}	200°C
Time (T _{SMIN} to T _{SMAX})	t _s	60-180 sec.
Temperature	T _L	217°C
Peak Temperature	T _P	260°C
Ramp-up rate	R _{UP}	3°C/sec max.
Ramp-down rate	R _{DOWN}	6°C/sec max.
Time within 5°C of Peak Temperature	t _p	10 sec.
Time t[25°C] to Peak Temperature	t[25°C] to Peak	480 sec.
Time	t _L	60-150 sec.

● ENVIRONMENTAL

PARAMETER	VALUE
MOISTURE SENSITIVITY LEVEL	1
RoHS	COMPLIANT
REACH SVHC	COMPLIANT
HALOGEN-FREE	COMPLIANT
ESD CLASSIFICATION LEVEL	N/A
TERMINATION FINISH	Au

